



[RC502 series]

| 피삭재 외경(mm) | 단 | | | |
|---------------|--------|-------|--------|-------|
| | RPM | FEED | RPM | FEED |
| 3 | 44,500 | 2,350 | 50,000 | 3,700 |
| 4 | 33,400 | 2,100 | 50,000 | 4,700 |
| 6 | 22,300 | 2,100 | 33,400 | 4,900 |
| 8 | 16,700 | 2,100 | 25,000 | 4,700 |
| 10 | 13,370 | 2,100 | 20,000 | 4,800 |
| 12 | 11,100 | 2,100 | 16,700 | 4,700 |

RPM = rev. / min.
FEED = mm / min.

[G series]

| 피삭재 외경(mm) | 단 | |
|---------------|--------|-------|
| | RPM | FEED |
| 0.5 | 16,000 | 480 |
| 0.75 | 16,000 | 640 |
| 1 | 16,000 | 800 |
| 1.5 | 16,000 | 1,450 |
| 2 | 16,000 | 2,100 |
| 3 | 15,000 | 2,950 |
| 4 | 13,000 | 3,000 |
| 5 | 11,500 | 3,050 |
| 6 | 10,500 | 3,150 |
| 8 | 8,555 | 2,960 |

RPM = rev. / min.
FEED = mm / min.

